
# C5 Series - LED Surface Luninaire



# Series No: C527-WT-LED-SB4



- O Slim, Compact Design
- © 35,000hours Lifetime

Light Distribution:

- © Excellent photometric performance
- O Low Maintenance Cost
- © 0 10v Dimmable available
- O Built-in self-contained emergency kit available



The C527 LED surface luminiare is an affordable alternative for fluorescent lamp, which provides high illumination in slim & compact design for use of general lighting and energy-saving solution

### Features:


- White/Grey Powder coated sheet steel body

Our Job Reference -香港專業教育學院沙田分校

- High-quality aluminium louver
- High CRI (>80 or 90)
- High Power Factor (>0.9)
- Energy Efficiency
- Long lifetime (35,000hrs)

# Standards:

- IEC/EN 60598-1,
- IEC/EN 60598-2-1
- IEC / EN60598-2-22
- IEC/EN 55015, IEC/EN 61547
- IEC/EN 61000-3-2,
- IEC/EN 61000-3-3



## Dimensions:

#### 

Model:	C527-WT-LED-SB4		
Rated Power:	25w		35w
Voltage:	200-240V AC 50/60Hz <0.9A		
Color Temp:	3000k	4000k	6000k
Lumen Output	(25w) 2400lm	(25w) 2500lm	(25w) 2650lm
	(35w) 3600lm	(35w) 3700lm	(35w) 3850lm
Dimenison:	L1185 x W78 x H75mm		
Operation Temp:	<b>-10 ~ 40</b> ℃		
CRI:	> 80 or >90		
Beam Angle:	140°		
Dimming Options:	0 - 10v Dimming		
Life time:	35,000hours		
Accessories	Ceiling Mounted Steel Wire + Fix Nut		